

DIGISTART 400

Ref. 10071



❓ The **DIGISTART 400** from **SOLTER** is the ultimate solution in professional chargers and starters. Designed for the most demanding environments, this unit delivers **superior power, increased charging capacity, and an advanced management system** that ensures unmatched performance. With its exclusive **10-stage intelligent charging curve**

Efficiency, robustness, and technology in a single unit!

Main Features:

- ❓ **High-performance charging:** Provides up to **60A** of charging current and a capacity of up to **500Ah**, optimizing battery maintenance for **12V** and **24V** systems.
- ❓ **Ultra-powerful starting function:** Up to **300A** of starting power, ideal for high-energy consumption vehicles.
- ❓ **Advanced repair mode:** Diagnoses and recovers **sulfated, inactive, or low-capacity batteries**, improving their performance.
- ❓ **10-stage charging curve:** An automated and safe process that maximizes battery efficiency and longevity.
- ❓ **Full compatibility:** Works with **WET, GEL, MF, EFB, and AGM** batteries, adapting to various needs.
- ❓ **Advanced safety system:** Protection against **overload, reverse polarity, and overheating**, ensuring safe and reliable use.
- ❓ **Integrated alternator test:** Allows checking the vehicle's charging system status.
- ❓ **Digital control panel:** LCD screen with **voltage indicator, charge percentage, and alternator diagnostics**.
- ❓ **Robust and portable design:** High-strength construction with **IP33** protection for enhanced durability in demanding environments.
- ❓ **Trust in SOLTER's innovation and quality for unlimited performance in your workshop or industry.**

DIGISTART 400

Ref. 10071



TECHNICAL DATA

OPTIONAL ACCESSORIES

Technical	
Capacidad de carga max.	500Ah
Corriente de carga Arith.	(DC 12V), 20A/30A/40A/60A o (DC 24V), 20A/30A/40A/60A
Tipo batería	WET (plomo-ácido), GEL, MF, EFB , AGM,
Voltaje de arranque	12/24V
Voltaje de carga	12/24V
Capacidad de arranque	300A

Structural	
Dimensions	290x600x250mm
Protection index	IP33
Regulation board	DIGISTART
Weight	18,3Kg

Electrical	
Supply Voltage	220-240VAC 50/60Hz
Absorbed power max.	3000W Max.(cargador), 9000W Max. (arranque)