

# AEROPROCESS C 400

Ref. 10110

 **SOLTER**



- Máquina de soldar profesional **MIG Sinérgico Multiproceso**.
- **400 amperios** al 30%.
- Modulo **Welding Itelligence (Wi)** integrado.
- Increíbles resultados en **todos los materiales** (Acero, Aluminio, Inoxidable, etc.).
- Incluye pinza de masa.

## Principales características:

- Máquina de hilo **multifunción** capaz de soldar mediante los procesos **MIG-MAG, TIG Lift-Arc y MMA**.
- Modulo **Wi** incorporado, con po
- Control sinérgico del proceso de soldadura con preselección del trabajo a realizar.
- Control de altura del arco para conseguir una soldadura **libre de proyecciones**
- **Crater-Filling regulable**, para un acabado del cordón de soldadura perfecto.
- Ideal para soldaduras con **GAP** (separación entre piezas)
- Posibilidad de **ajuste por velocidad de hilo (m/min.) y por corriente (Amp)**
- Lectura en tiempo real de tensión (Volt) e Intensidad (Amp) durante la soldadura. Al terminar, el equipo muestra el promedio de ambos parámetros.
- Control del consumo del hilo utilizado, permitiendo calcular el coste de cada proceso.
- Posibilidad de almacenar hasta **10 programas**
- Excelentes resultados con **programas pre-cargados** en la soldadura de: Acero al Carbono (SG3), Inoxidables (Ss-309, Ss-316), Aluminio (AL-5356, AL-4043), Cobre-Silicio (CuSi3) y Tubulares (Fc-Rutile, Fc-Basic, Fc-316)

# AEROPROCESS C 400

Ref. 10110



## TECHNICAL DATA

## OPTIONAL ACCESSORIES

### Generals

Duty Cycle at 40°C	30%
Regulation	10-400A
Intensity MAX.	400A
Intensity at 60%(100%) a 40°C	320A (280A)

### Technical

Usable electrodes TIG	1,6 - 4.0mm
Usable electrodes MMA	1,6 - 4,0mm
Usable wire coil	D300 - 15kg
Wire feeder rolls	4R
Motor max power	95W
Usable welding wire	0,6 - 1,6 mm

### Structural

Ventilation	DOUBLE AOUTOMATIC TUNNEL
Weight	36kg
Regulation board	AEROPROCESS SYNERGIC Wi
Standards	EN-90971-1, EN90974-10
Protection index	IP23S
Dimensions	920x270x640mm

### Electrical

I <sub>max</sub>	33A
OCV	62V
Voltage range	(360 - 440V)
Absorved power max.	22Kva
I <sub>eff</sub>	18A
Fuse	20A
Supply Voltage	400V - 3ph

Ref. 06029

### TORCH 4M TIG SR-26 D35/50



Ref. 06126

### CONJ. 3m Cu25mm 35-50 ELE 200A



Ref. 55603

### ROLL 1,0-1,2 30\*14mm ALU



Ref. 55604

### ROLL 0,8-1,0 30\*14mm TUB



Ref. 55605

### ROLL 1,2-1,6 30\*14mm TUB



Ref. 56033

### TORCH MIG 4M SX-36



Ref. 56077

### TORCH MIG 3M SX-36 ALU



Ref. 56210

### TIG ADAPTER AEROPROCESS



Ref. 56246

### GAS REGULATOR R25 AR/CO2

