

SOLCUT 50

Ref. 10133

 **SOLTER**

- **45Amp** plasma cutting equipment.
- **230V-1ph** connection.
- Cut up to **12mm**.
- Complete with **ground clamp** and torch.

- Highly portable and versatile **plasma cutting inverter** equipment thanks to its **230V-1ph** single-phase connection.
- With **maximum cutting** capacity and **clean cut** of up to **12 mm**, it is the ideal system for industrial maintenance and repair work.
- Cutting all types of materials such as **carbon steel, stainless steel** and **aluminum**.

SOLCUT 50

Ref. 10133



TECHNICAL DATA

OPTIONAL ACCESSORIES

Generals

Intensity at 60%(100%) a 40°C	40A (32A)
Intensity MAX.	45A
Regulations	EN 60974-1, EN 60974-10
Regulation	15 - 45A
Duty Cycle at 40°C	45A @ 50%

Technical

Cutting capacity ALUMINIUM	12mm
Cuttinh capacity STEEL	12mm
Cutting capacity STAINLESS STEEL	8mm
Air flow	150l/min
Air pressure	3,5 - 10bar
Optimal aire pressure	4,5 bar

Structural

Dimensions	504x213x314mm
Protection index	IP21
Weight	12 kg
Ventilation	FORZADA

Electrical

I ₁ max	23A
Absorved power max.	5Kva
Supply Voltage	230V - 1Ph
OCV	310V