


# SOLSPOT 9000+SPOT GUN+KIT STUDDER SOLTER

Ref. 10368



Spot welding machine with pneumatic spot gun to weld metal sheets up to 3+3mm and kit studder (dent puller)

Accessories included:

Pneumatic spot gun with extra-flexible copper cables L=2000 mm de 150 mm<sup>2</sup> and arms with electrodes of 107mm. Kit Studder (Gun with cables and complete kit of accessories and consumables) for dent pulling.

Trolley with wheels

Air pressure gouge

The SOLSPOT 9000 is an ideal machine for all types of bodywork repairs: spot welding of car and truck bodies and chassis (up to 3.0 + 3.0 mm), bodies repair with a spotter (dent puller), localized metal sheets heating (carbon electrode) for all types of steel, stainless steel and its alloys.

Controlled by a digital synchronous welding control with a double program, welding time adjustment with cycles and pulses, compensation and pulsation function for rusted and galvanized sheets and ongoing current adjustment (1 to 99 on the power scale) and welding time (1 to 99 cycles).

Simultaneous connection of the pneumatic spot gun and dent-puller pistol, with automatic recovery of the memorized welding program.

Unlike a conventional welding control, our control performs two different work cycles for the pneumatic spot gun and the dent puller, in addition the work cycle of the dent puller has the sheet heating function.

The control also manages the refrigeration unit with a pneumatic pump (Optional Ref: 10369).

It also allows the simultaneous connection of the pneumatic spot gun and the dent removal gun with automatic recovery of the corresponding memorized welding program, which saves time and avoids errors.

# SOLSPOT 9000+SPOT GUN+KIT STUDDER SOLTER

Ref. 10368

## TECHNICAL DATA

| Generals                  |            |
|---------------------------|------------|
| Intensity MAX.            | 8000A      |
| Technical                 |            |
| Potencia absorbida 50%    | 10Kva      |
| Voltaje de servicio (Vmp) | 8V         |
| Tiempo de soldadura       | 1-99       |
| Structural                |            |
| Weight                    | 105 kg     |
| Electrical                |            |
| Supply Voltage            | 400V - 1ph |
| Fuse                      | 25A        |
| Absorbed power max.       | 50Kva      |

## OPTIONAL ACCESSORIES


Ref. 10369

**WATER COOLING  
PNEUMATIC UNIT FOR  
SOLSPOT 9000**




Ref. 10381

**FOLDED ARMS COUPLE WITH  
ELECTRODES L= 107mm**




Ref. 10382

**FOLDED ARMS COUPLE WITH  
ELECTRODES L= 152mm**



Ref. 10383

**FOLDED ARMS COUPLE WITH  
ELECTRODES L= 235mm**




Ref. 10384

**FOLDED ARMS COUPLE WITH  
ELECTRODES L= 330mm**



Ref. 10385

**FOLDED ARMS COUPLE WITH  
ELECTRODES L= 480mm**




Ref. 10386

**ARMS COUPLE WITH  
ELECTRODES & FOLDED  
ELECTRODE L=107mm (ext)**



Ref. 10387

**ARMS COUPLE WITH  
ELECTRODES & FOLDED  
ELECTRODE L=107mm (int)**



Ref. 10388

**COUPLE OF SYMMETRICAL  
ARMS L= 250mm**



Ref. 10389

**ARMS COUPLE WITH  
STRAIGHT ELECTRODES L=  
107mm**



Ref. 10390

**ARMS COUPLE WITH  
STRAIGHT ELECTRODES L=  
235mm**



Ref. 10391

**ARMS COUPLE WITH  
STRAIGHT ELECTRODES L=  
332mm**



Ref. 10392

**ARMS COUPLE WITH  
STRAIGHT ELECTRODES L=  
483mm**



Ref. 10393

**ARMS COUPLE H= 200 L= 152  
WITH ELECTRODES**



Ref. 10394

**ARMS COUPLE H= 200 L= 235  
WITH ELECTRODES**



Ref. 10395

**ARMS COUPLE H= 200 L= 330  
WITH ELECTRODES**



Ref. 10396


**ARMS COUPLE H= 200 L= 480  
WITH ELECTRODES**



---

Ref. 10397

**ARMS COUPLE WITH  
REDUCED LIEN L= 330mm**



---

Ref. 30876

**CASQUILLO DE LATON  
BRAZOS D.18x18L**

